

Model		ADID-G4945UE	ADID-G5550UE
Size		49"	55"
Bezel width		3.5mm	3.5mm
Display	Resolution	1920X1080	1920X1080
	Contrast Ratio(typ)	3500:1	3500:1
	Brightness(typ)	450cd/m ²	500cd/m ²
	Color Depth	1.07 Billion(10bits)	1.06 Billion(10bits)
	Response time(typ)	8ms	8ms
	Viewing angle	H178°/V178°	H178°/V178°
Signal Interface	DVI-D	×1 (1920x1080, downward compatible)	×1 (1920x1080, downward compatible)
	HDMI	×2 (HDMI1 3840×2160@60Hz/HDMI2 3840×2160@30Hz, downward compatible)	×2 (HDMI1 3840×2160@60Hz/HDMI2 3840×2160@30Hz, downward compatible)
	DP INPUT	×1 (Loop input 3840×2160@60Hz, downward compatible)	×1 (Loop input 3840×2160@60Hz, downward compatible)
	DP OUTPUT	×1 (Loop output 3840×2160@60Hz, downward compatible)	×1 (Loop output 3840×2160@60Hz, downward compatible)
	VGA	×1 (1920x1080, downward compatible)	×1 (1920x1080, downward compatible)
	RJ45	×1 (RS232/IR Input)	×1 (RS232/IR Input)
	RJ45	×1(RS232 Output,IR Input)	×1(RS232 Output,IR Input)
Performance		DP Loop/4K input&output/90deg,180deg,270deg rotate/Support DPMS	DP Loop/4K input&output/90deg,180deg,270deg rotate/Support DPMS
Power supply		AC100V ~ 240V,50/60Hz	AC100V ~ 240V,50/60Hz
Power consumption(Max)		110W	200W
Power consumption(Standby)		<1W	<1W
Work environment		Temp.0 ⁰ C~40 ⁰ C/Hum.20%~80%	Temp.0 ⁰ C~40 ⁰ C/Hum.20%~80%
Storage environment		Temp.-10 ⁰ C~60 ⁰ C/Hum.5%~95%	Temp.-10 ⁰ C~60 ⁰ C/Hum.5%~95%
Mounting Options		wall-mounted/freestanding mount	wall-mounted/freestanding mount
Outline dimension (LXWXH:mm)		1077.6X607.8X106.7	1213.4X684.2X108.9
Display dimension (LXW:mm)		1073.8X604.0	1209.6X680.4
Weight		26kg	32kg
Life time (Avg.)		60000 hours	60000 hours

